

NEW

BIMEC®

Duplex Slitter Rewinder for Narrow Web



TBS/60

Taglierina Ribobinatrice a banda stretta ad avvolgimento centrale su due alberi, adatta per il taglio di films plastici carta ed accoppiati • Bobina madre su carro di svolgimento posteriore • Motori c.a. asincroni con inverter digitali • Avvolgimento su alberi frizionati • Controlli di tensione automatici e programmabili sia in svolgimento che in avvolgimento • Pannello operatore touchscreen per impostazione e visualizzazione dati e diagnostica • Comandi elettrici e pneumatici in comoda posizione per l'operatore • Svolgimento e avvolgimento a sbalzo per un carico e scarico rapido delle bobine

Duplex Slitter Rewinder for narrow web, suitable for slitting and rewinding plastic films, paper and laminates • Batch roll on unwind stand placed on the rear of machine • Asynchronous AC motors with digital inverters • Rewind on differential air shafts • Automatic and programmable tension controls both in unwinding and rewinding • Touchscreen operator panel for data setting and visualization and fault diagnostic • Electric and pneumatic controls easy to reach • Cantilevered open end design unwind and rewind for a quick loading and unloading of the rolls

DATI TECNICI / TECHNICAL DATA

TBS/60

Larghezza utili / Web width

610 mm

Diametro max bobina madre/ Max. batch roll diameter

800 mm

Diametro max bobine finite/ Max. finished roll diameter

610 mm

Larghezza di taglio min / Min. slitting width

10 mm

Velocità max macchina / Max. machine speed

500 mt/min

BIMEC®

BIMEC S.r.l.

Via Monte Grappa n° 9- 20020 VANZAGHELLO - MI - ITALY

Tel. ++39-0331-307491 - Fax. ++39-0331-307051 - infobimec@bimec.it - www.bimec.it